

SMART DEGAUSSER *MODEL: QDG-96A*



Specifications:

Key Features of QDG-96A

- QDG-96A unique waveform control capability delivers accurate demagnetizing current to draw magnetism to zero - your answer to complete degaussing of the cathode ray tubes.
- At a flip of a switch on the front panel, you can select full or adjustable degaussing strength - it gives you the flexibility to vary degaussing strength to cater to different sizes of CRTs.
- QDG-96A, now in its third generation of the product line, has improved reliability and repeatability. You get adequate power with precision control every time.

Degaussing Capacity:	Exceeding 4000AT p-p at full capacity using matching multi-turn coil
Variable Degaussing Capacity:	User-selectable from 10% to 90% of full capacity using thumb wheel switch
Output Peak Current:	Exceeding 25A Peak-to-Peak with 230VAC/50Hz using matching multi-turn coil
Degaussing Speed:	1 to 10 seconds adjustable using thumb wheel switch
Protection:	Protection for over current and over temperature
Remote Control:	External triggering for "start" and "variable-degauss-strength enable"
Dimension & Weight:	330x250x110mm 4.2 Kg
Power:	230VAC (115VAC version available on request)



46 Lorong 17 Geylang
 #05-02 Enterprise Industrial Building
 Singapore 388568
 Tel: 65 6745 3200
 Fax: 65 6745 9764
 Email: info@quantel.com.sg
 URL: www.quantel.com.sg